



064-023-2639
Environmentally
Preferred Flooring



CLICK PRO[®]

TWELVE WONDERS



Collection 2025/26

Floors For Great Interior



phthalate
free



formaldehyde
free



easy
maintenance



waterproof
surface



abrasion
resistant



underfoot
comfort



slip
resistant



sound
absorption



indentation
residual



stain
resistant



fire
reaction



residential &
commercial use



termite
retardant



antimicrobial
surface

Suitable for use in places with toddler (DOTP) and elderly (R9)

MATCHING FLOOR ACCESSORIES



PVC SKIRTING (PS Series)



PVC T - PROFILE (PT Series)



PVC END TRIM (PE Series)



PVC L - PROFILE
(PL Series)



TWELVE WONDERS



SW 55211 Yosemite



SW 55123 Giza



SW 55235 Comoe

NEW

Note : Miniature samples for colour illustration only

TWELVE WONDERS



SW 55161 Sequoia



SW 55158 Castle



SW 55283 Marseille

NEW

Note : Miniature samples for colour illustration only

TWELVE WONDERS



SW 55137 Jurassic

Colour Gradation Series



SW 55266 Cerrado



SW 55126 Windsor

Note : Miniature samples for colour illustration only

TWELVE WONDERS



SK 3658 T Mount Everest



SK 3663 T Fuji



SK 3636 T Beton

Note : Miniature samples for colour illustration only

CLICKPRO®

TWELVE WONDERS



Manufactured under a management system in compliance with ISO 9001 & ISO 14001



The Benefits

CLICKPRO planks and tiles are high performance floating floor made from high quality vinyl. The aesthetics of hard wood and natural stone are now combined with the resistance of pure vinyl to scratches, scuffing, stain and dirt. CLICKPRO surface is impervious to water and can be deployed in places that receive spills. With its slip resistance surface and underfoot resilience, you can enjoy walking on it barefoot. Being glueless, it is also eco friendly to install and contributes to improved indoor air quality. The aesthetics are unsurpassed with the natural wood emboss and non-repeat wood pattern at the two ends of each plank and tile. The surface is treated with antimicrobial protective coating. CLICKPRO LVT click offers superior impact sound insulation as compared to other click system such as SPC and laminated floors. With easy maintenance, CLICKPRO are floors for great interior.

Application

CLICKPRO can be installed in the residential and general commercial environment. In residential, it can be fitted in the bedroom, study, living and dining area. It can also be installed in dry kitchen and entrance of bathroom by sealing the perimeter edges with silicon caulk. It can be readily installed over existing hard surfaces and in moisture prone area where wood flooring and glue-down products are off limit. For commercial use, with its 0.5mm high performance wear layer, CLICKPRO is well suited for use in offices, care centres, retail outlets and institutions.

Installation & Care

Before install check list *Substrate must be structurally stable, flat and smooth. *Check floor level variation is <3.0mm across any 1.2 meters. *Check subfloor moisture level must be <90%RH. *Floor to be acclimatized on site 12 hours at room temperature before installing. *Height variation between ceramic tiles, plywood and any other existing flooring must be patched and levelled before laying over with new click flooring. *For areas with rolling load and high foot traffic, thicker product thickness should be used. *All carton boxes, planks and tiles must be stored completely flat on hard surface.

During install check list *For every 5 meters room length, leave a 2mm wall gap. *Leave an expansion gap every 15 meters. *All joints must be properly adjoined. *For wet area use, fill the perimeter gaps with high quality silicone caulking.

Notes to end user *Do not spread excess water such that they seep into wall gaps. *Avoid exposure to long period of peak hours direct sunlight without protection of shades. *Do not drag heavy furniture across the surface. *For the use of chair with castor wheel, a protective surface pad is recommended.

Maintenance *Floors should be swept or vacuum regularly to remove loose dirt. *Damp mop as needed using clean water and a PH neutral floor cleaner. Cleaner should be free of ammonia and hydrochloric acid. *Aging floor can be restored by machine buffing and polishing.

Product Specifications

CLASSIFICATION	STANDARDS		TWELVE WONDERS
Size	EN 427	mm	Plank : 178 x 1219 mm Tile : 305 x 610 mm
Thickness *	EN 428	mm	5.0 mm (Micro-Bevelled Edge)
Wear layer *	EN 429	mm	0.50 mm
Curling *	EN 434	mm	≤2 mm
Packing	-	Carton	8 planks / box (1.73m ²) 9 tiles / box (1.67m ²)
Dimensional stability *	EN 434	%	X direction: ≤0.25 Y direction: ≤0.25
Residual Indentation *	EN 433	mm	≤0.1mm
Effect of castor chair *	EN 425	-	No visible damage
Abrasion resistance *	EN 660	mm ³	Wear Group T. Fv ≤ 2.0
Slip resistance *	SS 485 (Dry friction test) SS 485 (Wet friction test)	-	Coefficient of friction: ≥0.4 Classification: X (35 to 44)
Sound insulation	ISO 10140 / ISO 717-2	dB	ΔLw = 12, CiΔ = -7
Colour fastness *	ISO 105-B02	Degree	> 6
Stain resistance *	EN 423	Index	Complied
Fire classification *	EN 13501-1	Class	Bfl-S1 (flame spread / smoke)
Electrical propensity	EN 1815	kV	< 2
Cigarette burn resistance *	EN 1399	Class	Class 3
Classification (level of use)	EN 429	Class	Heavy domestic (class 23) General commercial (class 32)
Formaldehyde emission	EN 717-1	mg/m ²	Not detected
Heavy metal	EN 71 Part 3	mg/kg	Not detected
Pentachlorophenol	14041	mg/kg	Not detected
Phthalate	EN 14372 : 2004	mg/kg	Not detected
Antimicrobial activities	ISO 22196	Bacteria	>99% reduction (ATCC 6538P / 8739)
	ISO 846	Fungi	No growth observed (ATCC 6205 / 6275 / AS3.2942 / 3875 / 3984)

* Complies with Singapore HDB Material Listing performance criteria, other test standards are additional. CLICKPRO offers a 10 years residential wear durability and 3 years commercial limited warranty against manufacturing defects. By following the installation and care, CLICKPRO will provide a beautiful and lasting floor for many years to come.